

# QUANTERRA



The Q330S is an advanced 3 or 6 channel broad-band, high resolution ultra-low-power seismic system incorporating Quanterra's proven IP networking technology and super rugged USB flash recording. The Q330 uses Quanterra's exclusive patented (US Patent 4866442, Japan Patent 2787445, others pending) delta-sigma 24-bit A/D with DSP, and includes 32Mb RAM, GPS receiver, USB recording, power management, sensor command/control, and an advanced telemetry application for reliable data delivery.

#### **Streamlined Remote Administration**

The Q330S is designed for simple network maintenance and administration, before, during, and after deployment. Internet security is built-in. Proven UDP and TCP communications modes are standard.

#### **Telemetry...and Local USB Recording**

The Q330S supports real-time data telemetry to multiple central sites and simultaneous local recording on rugged USB flash media. The peerless performance of the Quanterra Q330 in the IRIS/USArray program has established an unchallenged reputation for delivery of high quality data.

#### **Rugged USB Media - MSEED**

FDSN-standard MSEED recorded on dual USB media. The media are housed in a rugged watertight compartment.

## Q330S

### VERY LOW-POWER HIGH-RESOLUTION INTEGRATED SEISMIC SYSTEM

#### FEATURES

##### **Low! Power**

Incorporating the latest low-power technology, the Q330S achieves integrated capability with an average power requirement of <0.75W, including recorder & GPS!

##### **Internet-Ready Industry Standards**

The ultra-reliable Q330S telemetry protocols have been proven in thousands of world-wide installations, and enable the use of off-the-shelf IP equipment and service providers. Dual Ethernet interfaces 10BaseT and 100BaseT are built-in. Data recorded on local media may be accessed using simple standard protocols including HTTP, FTP, and SSH.

##### **Comprehensive Sensor Control**

The Q330S is a seismological instrument, not a digitizer alone. Sensor control interface, including advanced sensor calibration, and sensor identification-tag support is built in.

#### SPECIFICATIONS

<b>Channels</b>	3- or 6-channel	<b>Sample Rate</b>	200, 100, 50, 40, 20, 10, 1 Other rates available.
<b>Dynamic Range</b>	132-135 dB wideband RMS typical Typical band-limited 136 dB	<b>Time Base</b>	Precision TCXO, locked to GPS. No adjustment.
<b>Format</b>	2-bit integer, Level 2 compressed 1-second packets	<b>DSP/CPU</b>	ADSP-2189M & EP9302
<b>Input Range</b>	40V P-P at gain=1	<b>Telemetry</b>	Full Duplex, efficient positive acknowledge with error control. UDP or TCP IP over Ethernet. Burst or continuous. Operates with major application software.
<b>Gain</b>	Selectable per channel: 1,30	<b>Temperature</b>	Fully specified -20 to +50C Operative -40 to +70C
<b>Filtering</b>	Linear or Minimum Phase FIR.		

# QUANTERRA

## SPECIFICATIONS

<b>Operational</b>	Temp, DC voltage, GPS status, Sensor boom position (6 chan)
<b>Memory</b>	32Mb RAM standard
<b>Network</b>	Dual Ethernet (10BT & 10/100BT) Full IP Protocol Stack (Linux)
<b>Serial Ports</b>	1 console ports up to 115kbaud.
<b>Media</b>	Dual USB up to 32G total, failover. -40 +70 rated media available.
<b>Wireless</b>	IrDA interface supported.
<b>Power</b>	<0.6 W avg. 12VDC 3-channel <0.8 W avg. 12VDC 6-channel Add 1.2W for continuous operation. Other dynamic dependencies.
<b>Physical</b>	Sealed, Aluminum, 17 X 4 X 6 in., 9 lbs., Rubber endcaps, Externally visible status and fault indicators.